

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 8805-1 (1978): General requirements for ferrule type couplings used in oil-hydraulic system, Part 1: General [PGD 17: Fluid Power Fittings, Hoses and Hose Assemblies]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



Indian Standard
**GENERAL REQUIREMENTS FOR FERRULE
 TYPE COUPLINGS USED IN OIL-HYDRAULIC SYSTEMS**
PART I GENERAL
 (Incorporating Amendment Nos. 1, 2 & 3)

1. Scope — Specifies the requirements for ferrule type couplings for tube with outside diameter of tube from 4 mm to 42 mm used in oil-hydraulic systems.

2. Working Principles — A coupling body, a coupling nut and a ferrule when assembled with a tube forms a joint. After the alignment of the body, nut and ferrule with the tube, the nut is progressively tightened causing the ferrule to move along with the nut. On tightening, the force exerted uniformly makes the ferrule to bite onto the tube. Thus the ferrule is made to throw up in front of it a ridge of displaced metal, which acts as a metallic interlock and gives the joint the pressure holding quality (see Fig. 1 and 2).




FIG. 1 BEFORE TIGHTENING OF COUPLING NUT

FIG. 2 AFTER TIGHTENING OF COUPLING NUT

2.1 On making of the joint, the ferrule is altered in shape and its leading edge becomes embedded in the tube. When the joint is broken the ferrule remains permanently attached to the tube end, and because of this, the joint can be dismantled and remade without affecting sealing characteristics for a number of times. In addition to acting as a sealing member the ferrule also functions as a spring washer between the nut, the body portion and the surface of the tube which helps the joint to remain pressure tight even during heavy vibrations.

3. Tube Sizes — Tubes having the outside diameter and tolerances specified in Table 1 and suitable to withstand the desired pressure shall be chosen.

TABLE 1 TOLERANCES ON TUBE SIZES (All dimensions in millimetres)	
Outside Diameter of Tube	Tolerance
4	± 0.1
6	
8	
10	
12	
14	
15	
16	
18	
20	
22	
25	
28	
30	
35	± 0.15
38	
42	± 0.2

Adopted 14 February 1978

© BIS 2003

Price Group 3

BUREAU OF INDIAN STANDARDS
 MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
 NEW DELHI 110002

IS : 8805 (Part I) - 1978

4. Working Pressure — The minimum working pressures for couplings used at temperatures between -10°C and $+120^{\circ}\text{C}$ shall be as given in Table 2. For applications involving other working temperatures, the working pressures shall be subject to agreement between the purchaser and the manufacturer.


TABLE 2 GENERAL OUTLAY OF PRESSURE RANGES, TUBE SIZES AND THREADS

Series	Outside Dia of Tube mm	Nominal Bore of Tube mm	Working Pressure MN/m^2 (kgf/cm^2)	Thread Size at Port/Stud End (Pipe Threads)
Light L	4	3	3.9 (40)	1/8
	6	5	24.5 (250)	1/8
	8	6		1/4
	10	8		1/4
	12	10		3/8
	15	12		1/2
	18	16	15.7 (160)	1/2
	22	20	9.8 (100)	3/4
	28	25		1
	35	32		1 1/4
	42	40		1 1/2
Heavy H	6	3	39.2 (400)	1/4
	8	4		1/4
	10	6		3/8
	12	8		3/8
	14	10		1/2
	16	12		1/2
	20	16		3/4
	25	20	24.5 (250)	1
	30	25		1 1/4
	38	32		1 1/2

5. Port Details — The types and details of threads for ports shall be as given in Table 3.

TABLE 3 DIMENSIONS AND TYPES OF THREADS FOR PORTS

All dimensions in millimetres



PORT END FORM X
(FOR STUD ENDS OF TYPES A, B AND C)

PORT END FORM Y
(FOR STUD END OF TYPE C)


d_1	$d_2 + \frac{0.4}{0}$	a_1 Max	b_1	b_2	t_1 Min	t_2 Min
G 1/8	15	1	8	5.5	13	9.5
G 1/4	19	1.5	12	8.5	18.5	13.5
G 3/8	23	2	12	8.5	18.5	13.5
G 1/2	27	2.5	14	10.5	22	16.5
G 3/4	33	2.5	16	13	24	19
G1	40	2.5	18	—	27	—
G1 1/4	50	2.5	20	—	29	—
G1 1/2	56	2.5	22	—	31	—

Note — The internal threads shall be parallel pipe threads according to IS : 2643-1975 'Dimensions for pipe threads for fastening purposes'. The threads shall not be truncated.

6. Details of Stud End for Couplings — The types and details of stud end for couplings shall be as given in Table 4.

TABLE 4 DIMENSIONS AND TYPES OF STUD ENDS FOR COUPLINGS

All dimensions in millimetres



d_1^* Type A and B	$d_2^†$ Type C	d_3 h14	d_4 0 -0.3	d_5 0 -0.5	a_1 Min	f_1 +0.3 -0.2	g_1 0 -0.5	l_1 ± 0.2	l_2 Min	R	Outside Dia of Tube for Series	
											L	H
G 1/8	R 1/8	14	10	13	1.5	2	8.3	8	8	1	4/6	—
G 1/4	R 1/4	18	13.4	17	2	3	11.2	12	12	1.2	8/10	6/8
G 3/8	R 3/8	22	17	21	2.5	3	14.7	12	12	1.2	12	10/12
G 1/2	R 1/2	26	21.3	25	3	4	18.4	14	14	1.6	15/18	14/16
G 3/4	—	32	26.7	30	3	4	23.9	16	16	1.6	22	20
G 1	—	39	33.5	37	3	5	29.9	18	—	2.5	28	25
G 1 1/4	—	49	42.2	47	3	5	38.6	20	—	2.5	35	30
G 1 1/2	—	55	48.1	53	3	5	44.5	22	—	2.5	42	38

*The threads on Type A and B shall be external pipe threads of tolerance class A of IS 2643-1975

†The threads on Type C shall be external taper pipe threads to IS 554-1975 'Dimensions for pipe threads where pressure tight joints are required on the threads (second revision)'

7. Details of Tube End for Couplings — The details of tube end for couplings shall be as given in Table 5.

8. General Requirements

8.1 Workmanship — Coupling shall be cleanly and neatly finished, free from burrs, fins, sharp edges and other defects.

8.2 Surface Protection — As specified in individual standards.


8.3 Marking — Each coupling shall be clearly marked with size (outside dia of tube) and series (letter L or H).

8.3.1 ISI Certification Marking — Details available with the Indian Standards Institution.

TABLE 5 DIMENSIONS OF TUBE END FOR COUPLINGS

(Clause 7)

All dimensions in millimetres



Series	Outside Dia of Tube	D	d	d ₁ B 11	d ₂ +0.1 0	l ±0.2	h +0.3 0
Light L	4	M 8 × 1	3	4	5	8	4
	6	M 12 × 1.5	4	6	8.1	10	7
	8	M 14 × 1.5	6	8	10.1	10	7
	10	M 16 × 1.5	8	10	12.3	11	7
	12	M 18 × 1.5	10	12	14.3	11	7
	15	M 22 × 1.5	12	15	17.3	12	7
	18	M 26 × 1.5	15	18	20.3	12	7.5
	22	M 30 × 2	19	22	24.3	14	7.5
	28	M 36 × 2	24	28	30.3	14	7.5
	35	M 45 × 2	30	35	38	16	10.5
Heavy H	42	M 52 × 2	36	42	45	16	11
	6	M 14 × 1.5	4	6	8.1	12	7
	8	M 16 × 1.5	5	8	10.1	12	7
	10	M 18 × 1.5	7	10	12.3	12	7.5
	12	M 20 × 1.5	8	12	14.3	12	7.5
	14	M 22 × 1.5	10	14	16.3	14	8
	16	M 24 × 1.5	12	16	18.3	14	8.5
	20	M 30 × 2	16	20	22.9	16	10.5
	25	M 36 × 2	20	25	27.9	18	12
	30	M 42 × 2	25	30	33	20	13.5
	38	M 52 × 2	32	38	41	22	16

Note 1 — For undercut details refer IS 1369-1975 'Dimensions of screw thread runouts and undercuts'

Note 2 — For values of chamfer Z refer IS 1368-1967 'Dimensions of ends of bolts and screws'

Note 3 — Threads for dia D shall conform to class 6g of IS 4218 (Part IV)-1976 ISO metric screw threads Part IV Tolerancing system (first revision)

9. Test Requirements

9.1 Hydraulic Test Requirements of Assembled Joint — When agreed between the purchaser and the manufacturer, a coupling, selected to represent a batch of couplings, shall be assembled as a joint and subjected to an internal pressure at least 1½ times the working pressure of the system. The tubing used for the assembled joint shall be representative of that to be installed with the couplings. The test fluid, test pressure, method and duration of test shall be agreed between the purchaser and the manufacturer.

9.1.1 When so tested, the assembled joint shall show no sign of leakage.

9.2 Dismantling and Re-assembly — The coupling shall be capable of having the joint dismantled and remade six times and shall provide a sound joint on each occasion and shall, on each re-assembly, be tested as specified in 9.1.

EXPLANATORY NOTE

This standard would be finally prepared in three parts. The other parts of the standard are:

Part II Survey of coupling assemblies and assembly procedure

Part III Test requirements

In the preparation of this part of the standard, considerable assistance has been derived from the following:

BS 4368 Part 1 Carbon and stainless steel compression couplings, heavy series (metric),

BS 4368 Part 3 Carbon and stainless steel compression couplings, light series (metric);

DIN 2353 — Non soldered, taper bush type unions, complete unions and survey; and

DIN 3852 Blatt 2 — Screwed plugs, tapped holes, with whitworth pipe threads, general outlay of types

This edition 1.3 incorporates Amendment No. 1 (April 1981), Amendment No. 2 (April 1985) and Amendment No. 3 (June 1995). Side bar indicates modification of the text as the result of incorporation of the amendments.